

Alarm Flash Light (EX)

Type: CWB-ATEX-EH ST

1. Technical Data

Length:	approx. 283 mm (incl. cable gland)
Width:	150 mm
Height:	approx. 129 mm
Weight:	2,2 kg
Type of protection:	IP 66
Material of cabinet:	Cap: polycarbonate Cabinet: Aluminum AlMgSi1
Ambient temperature range:	-20°C – +50°C
Colour of cap:	blue
Cable gland:	1x M20 x 1,5 (ATEX de)
Pulg Cap:	1x M20 x 1,5 (ATEX de)
Drawing No:	3.06087.10
EC – Type Examination Certificate:	LCIE 02 ATEX 6113
Group, Category, Type of Protection:	⊕ Ex II 2 G EEx de IIC T5 Tamb < 50°C T6 Tamb < 40°C ⊕ Ex II 2 D IP66 T85°C Tamb < 40°C T100°C Tamb < 50°C
Statement of Conformity:	CE 0344 according to 94/9 EG

2. Electrical Data

Power supply:	12 – 48 V DC +/- 10 %
Current consumption:	300 500 mA
Flash energy:	5 Joule
Flash frequency:	1 Hz
Service life:	8 x 10 ⁶ flashes

EC – Type Examination Certificate, Statement of Conformity, Declaration of Conformity and instructions have to be observed.
For information see www.pfannenbergl.com.

3. Varnish

powder-coated, yellow / black