

AEROSOL Fire Extinguishing Generator

(with thermal activator)
Type: Dynameco 2000-TA08

1. Specifications

Dimensions:	H _{max.} = 401 mm (with optional End-Position Switch) H = 311 mm (w/o optional End-Position Switch) d = 200 mm W _{max.} = 206 mm
Total weight:	approx. 8.42 kg (with optional End-Position Switch) approx. 8.35 kg (w/o optional End-Position Switch)
Duration of AEROSOL generation:	approx. 15 s
Volume to be protected:	approx. 20 m ³
P/N:	40 206

2. System Specific Data

Activation temperatures of thermal activators:	57°C: orange glass ampoule, 68°C: red glass ampoule, 79°C: yellow glass ampoule, 93°C: green glass ampoule, (other temperature ranges on request)
Ignition time:	3 seconds after activation with the glass ampoule
Storage:	cool and dry
Max. operation temperatures and storage temperatures:	42°C: orange glass ampoule, 53°C: red glass ampoule, 64°C: yellow glass ampoule, 78°C: green glass ampoule
General operation temperatures and storage temperatures:	-40°C to max. 15°C below stated activation temperature of the built-in thermal activator
Fire Class:	A, B, F (limited) and C according to DIN EN2
<u>Approvals:</u>	Federal Institute (of Germany) for Materials Research and Testing: BAM-PT1-1741 Ministry of Interior of Nordrhein-Westfalen: No. PL-4/97

3. Service Specific Data

Maximum period of use or latest exchange date:	5 years from the date of delivery (see inspection sticker)
--	---

4. Optional functional extension

potential-free feedback contact "Released":	End-Position Switch (potential-free NC contact), which is prepared with a HT connection cable AWG 20 (2x0.62 ²) (-40°C to +150°C) having a standard length of 2 m by the factory. Type: Dynameco TA08-ES, P/N: 80 500
---	--

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date 11/02/2017

Version 1/W.HR

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No

4.13262.5-1

Page 1 of 1