

AEROSOL Fire Extinguishing Generator


(with pneumatic activation)

Type: Dynameco 200-PA01

1. Specifications

Dimensions:	$H_{max.}$	= 305 mm (with the Straight Screw Connector Type: PA01-GSTR, P/N: 30 547 and sensor tube, under the consideration of the minimum bend radius of the sensor tube)
	H_T	= 215 mm (with T-Screw Connector Type: PA01-TSTR, P/N: 30 549)
	H_{90°	= 215 mm (with the Angle Screw Connector Type: PA01-WSTR, P/N: 30 548)
	H	= 195 mm (without screw connector)
	d	= 82 mm
	$d_{max.}$	= 88 mm
Total weight:		approx. 1.16 kg
Duration of AEROSOL generation:		approx. 5 s
Volume to be protected:		approx. 2 m ³
P/N:		40 260

2. System Specific Data

Sensor tube to be used:	Type: PA01-SNS 4x6, P/N: 50 394
System pressure:	nominal: 15 bars max.: 20 bars
Start of the effect:	immediately after the activation of the pneumatic trip system
Storage:	cool and dry
Operating temperature range:	-40°C to +85°C
Max. operating temperature range with sensor tube:	-40°C to +80°C
Fire class:	A, B, F (limited) und C according to DIN EN2
EMC-Testing:	e12 02 0017
Approvals: 	German Lloyd (GL) No. 44 242-07 HH Ministry of Interior of Nordrhein-Westfalen: No. PL-4/97

3. Service Specific Data

Maximum period of use or latest exchange date:	5 years from the date of delivery (see inspection sticker)
--	---

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date

11/02/2017

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No

4.13263.3-1

Version

1/W.HR

Page 1 of 1