

UV-Flame Detector

Type: FL/SS 7510/35

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatsoever is not permitted without written authority from the proprietors.

1. Technical Data

Length:	140 mm
Width:	95 mm
Depth:	82 mm
Housing material:	aluminum die-casting; G-ALSi 10 Mg
Weight:	0.7 kg
Protection type:	IP 54
Optics:	40 x 40
Angle of view:	90° horizontal, 90° vertical
Operating temperature range:	-10°C to +85°C
Connection:	Si-S1-0 6 x 0.5 approx. 1 m long

2. Electrical Data

Supply voltage:	15 VDC
Current consumption	
Operational readiness:	approx. 0.08 A

3. Output voltages

Fire alarm:	max. 15 VDC
Voltage monitoring:	max. 15 VDC
Pollution monitoring:	max. 15 VDC

Connection of the detector only to the evaluation board AWK 880

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date

04/01/1985

Version

1/P.BO

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No

BS4.5091-1

Page 1 of 1