

AEROSOL Fire Extinguishing Generator
(with electrical ignition)
Type: Dynameco 2000-E02

1. Specifications

Dimensions: $H_{max.}$ = 269 mm (incl. circlip)
 H = 262 mm (without circlip)
 d = 200 mm
 $W_{max.}$ = 206 mm

Total weight: approx. 8.25 kg

Duration of AEROSOL generation: approx. 15 s

Volume to be protected: approx. 20 m³

P/N: 40 144

2. System Specific Data

Electrical ignition: 1.5 A; 6 ms

Internal resistance: 0.9Ω ± 0.1Ω

Ignition time: without time lag

Storage: cool and dry

Operation temperature: -40 °C to +85 °C

Certification: BAM-PT₁ - 0567

Fire Class: A, B, F (limited) and C according to DIN EN2

EMV-approval: e12 02 0017

Approval mark: PL-4/97

3. Service Specific Data

Maximum period of use or latest exchange date: 5 years from the date of delivery
(see inspection sticker)

All rights strictly reserved except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietors.



Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Date 11/02/2017

Version 7/W.HR

EGON HARIG GmbH
Gewerbering 4 • D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Datasheet No

4.06097-1

Page 1 of 1